

Rorinks

2025

Selection Guide

RORINKS ELECTRONIC CO., LTD.

Mail: 15764145@qq.com

Website : www.rorinks.com

HDR series din rail power supply



Features:

- Input full range
- 85-264VAC/120~370VDC
- 47-63Hz
- Working temp:-10~+50°C
- Dimension:17.5*90*54.5MM
- Weight:0.08KGS
- 3 years warranty



Features:

- Input full range
- 85-264VAC/120~370VDC
- 47-63Hz
- Working temp:-10~+50°C
- Dimension:35*90*54.5MM
- Weight:0.12KGS
- 3 years warranty

Model	DC output	Current	Efficiency
HDR-15-5	5V	2.4A	78%
HDR-15-12	12V	1.25A	83%
HDR-15-24	24V	0.63A	84%
HDR-15-48	48V	0.32A	85%

Model	DC output	Current	Efficiency
HDR-30-5	5V	3A	80%
HDR-30-12	12V	2A	86%
HDR-30-24	24V	1.5A	87%
HDR-30-48	48V	0.75A	87%



Features:

- Input full range
- 85-264VAC/120~370VDC
- 47-63Hz
- Working temp:-10~+50°C
- Dimension:52.5*90*54.5MM
- Weight:0.19KGS
- 3 years warranty



Features:

- Input full range
- 85-264VAC/120~370VDC
- 47-63Hz
- Working temp:-10~+50°C
- Dimension:70*90*54.5MM
- Weight:0.27KGS
- 3 years warranty

Model	DC output	Current	Efficiency
HDR-60-5	5V	6.5A	82%
HDR-60-12	12V	4.5A	85%
HDR-60-24	24V	2.5A	88%
HDR-60-48	48V	1.25A	88%

Model	DC output	Current	Efficiency
HDR-100-12	12V	7.5A	86%
HDR-100-15	15V	6.5A	86%
HDR-100-24	24V	4.2A	88%
HDR-100-48	48V	2.1A	88%

EDR series din rail power supply



Features:

- Input full range
- 85-264VAC/120~370VDC
- 47-63Hz
- Working temp:-10~+50°C
- Dimension:32*125.2*102MM
- Weight:0.51KGS
- 3 years warranty



Features:

- Input full range
- 85-264VAC/120~370VDC
- 47-63Hz
- Working temp:-10~+50°C
- Dimension:40*125.2*113.5MM
- Weight:0.6KGS
- 3 years warranty

Model	DC output	Current	Efficiency
EDR-75-12	12V	6.3A	85%
EDR-75-24	24V	3.2A	88%
EDR-75-36	36V	2.1A	89%
EDR-75-48	48V	1.6A	89%

Model	DC output	Current	Efficiency
EDR-120-12	12V	10A	85%
EDR-120-24	24V	5A	87%
EDR-120-36	36V	3.4A	87%
EDR-120-48	48V	2.5A	88%

NDR series din rail power supply



Features:

- Input full range
- 85-264VAC/120~370VDC
- 47-63Hz
- Working temp:-10~+50°C
- Dimension:32*125.2*102MM
- Weight:0.51KGS
- 3 years warranty



Features:

- Input full range
- 85-264VAC/120~370VDC
- 47-63Hz
- Working temp:-10~+50°C
- Dimension:40*125.2*113.5MM
- Weight:0.6KGS
- 3 years warranty

Model	DC output	Current	Efficiency
NDR-75-12	12V	6.3A	85%
NDR-75-24	24V	3.2A	88%
NDR-75-36	36V	2.1A	89%
NDR-75-48	48V	1.6A	89%

Model	DC output	Current	Efficiency
NDR-120-12	12V	10A	85%
NDR-120-24	24V	5A	88%
NDR-120-36	36V	3.4A	89%
NDR-120-48	48V	2.5A	89%



Features:

- Input full range
- 85-264VAC/120~370VDC
- 47-63Hz
- Working temp:-10~+50°C
- Dimension:63*125.2*113.5MM
- Weight:1KGS
- 3 years warranty



Features:

- Input full range
- 85-264VAC/120~370VDC
- 47-63Hz
- Working temp:-10~+50°C
- Dimension:85.5*125.2*128.5MM
- Weight:1.5KGS
- 3 years warranty

Model	DC output	Current	Efficiency
NDR-240-24	24V	10A	88%
NDR-240-36	36V	6.6A	89%
NDR-240-48	48V	5A	89%
NDR-240-60	60V	4A	90%

Model	DC output	Current	Efficiency
NDR-480-24	24V	20A	92%
NDR-480-36	36V	13.3A	92%
NDR-480-48	48V	10A	92%
NDR-480-60	60V	8A	92%



Features:

- Input full range
- 85-264VAC/120~370VDC
- 47-63Hz
- Working temp:-10~+50°C
- Dimension:40*125.2*113.5MM
- Weight:0.6KGS
- 3 years warranty



Features:

- Input full range
- 85-264VAC/120~370VDC
- 47-63Hz
- Working temp:-10~+50°C
- Dimension:63*125.2*113.5MM
- Weight:1KGS
- 3 years warranty

Model	DC output	Current	Efficiency
EDR-150-24	24V	6.5A	85%
EDR-150-36	36V	4.2A	86%
EDR-150-48	48V	3.2A	87%
EDR-150-60	60V	2.5A	87%

Model	DC output	Current	Efficiency
EDR-240-24	24V	10A	87%
EDR-240-36	36V	6.6A	87%
EDR-240-48	48V	5A	88%
EDR-240-60	60V	4A	88%

MDR series mini din rail power supply



Features:

- 85-264VAC/120~370VDC
- 47-63Hz
- Working temp:-20~+70°C
- Dimension:99*82*30MM
- Weight:0.23KGS
- 3 years warranty



Features:

- Input full range
- 85-264VAC/120~370VDC
- 47-63Hz
- Working temp:-10~+50°C
- Dimension:22.5*90*100MM
- Weight:0.19KGS
- 3 years warranty

Model	DC output	Current	Efficiency
MDR-10-5	5V	2A	77%
MDR-10-12	12V	0.84A	81%
MDR-10-15	15V	0.6A	82%
MDR-10-24	24V	0.42A	84%

Model	DC output	Current	Efficiency
MDR-20-5	5V	3A	76%
MDR-20-12	12V	1.67A	80%
MDR-20-15	15V	1.34A	81%
MDR-20-24	24V	1A	84%

DR series din rail power supply



Features:

- Input full range
- 85-264VAC/120~370VDC
- 47-63Hz
- Working temp:-10~+50°C
- Dimension:78*93*56MM
- Weight:0.27KGS
- 3 years warranty



Features:

- Input full range
- 85-264VAC/120~370VDC
- 47-63Hz
- Working temp:-10~+50°C
- Dimension:78*93*56MM
- Weight:0.27KGS
- 3 years warranty

Model	DC output	Current	Efficiency
DR-30-5	5V	3A	74%
DR-30-12	12V	2A	81%
DR-30-24	24V	1.5A	83%
DR-30-48	48V	0.62A	83%

Model	DC output	Current	Efficiency
DR-45-5	5V	5A	72%
DR-45-12	12V	3.5A	77%
DR-45-24	24V	2A	80%
DR-45-48	48V	0.93A	80%



Features:

- Input full range
- 85-264VAC/120~370VDC
- 47-63Hz
- Working temp:-10~+50°C
- Dimension:52.5*90*54.5MM
- Weight:0.19KGS
- 3 years warranty



Features:

- Input full range
- 85-264VAC/120~370VDC
- 47-63Hz
- Working temp:-10~+50°C
- Dimension:22.5*90*100MM
- Weight:0.33KGS
- 3 years warranty

Model	DC output	Current	Efficiency
MDR-40-5	5V	6A	78%
MDR-40-12	12V	3.33A	86%
MDR-40-24	24V	1.7A	88%
MDR-40-48	48V	0.83A	88%

Model	DC output	Current	Efficiency
MDR-60-5	5V	10A	76%
MDR-60-12	12V	5A	84%
MDR-60-24	24V	2.5A	86%
MDR-60-48	48V	1.25A	86%



Features:

- Input full range
- 85-264VAC/120~370VDC
- 47-63Hz
- Working temp:-10~+50°C
- Dimension:78*93*56MM
- Weight:0.3KGS
- 3 years warranty



Features:

- Input full range
- 85-264VAC/120~370VDC
- 47-63Hz
- Working temp:-10~+50°C
- Dimension:55.5*125.5*100MM
- Weight:0.55KGS
- 3 years warranty

Model	DC output	Current	Efficiency
DR-60-5	5V	6.5A	76%
DR-60-12	12V	4.5A	82%
DR-60-24	24V	2.5A	84%
DR-60-48	48V	1.25A	84%

Model	DC output	Current	Efficiency
DR-75-12	12V	6.3A	76%
DR-75-15	15V	5A	80%
DR-75-24	24V	3.2A	80%
DR-75-48	48V	1.6A	81%



Features:

- Input full range
- 85-264VAC/120~370VDC
- 47-63Hz
- Working temp:-10~+50°C
- Dimension:32*125.2*102MM
- Weight:0.51KGS
- 3 years warranty



Features:

- Input full range
- 85-264VAC/120~370VDC
- 47-63Hz
- Working temp:-10~+50°C
- Dimension:22.5*90*100MM
- Weight:0.17KGS
- 3 years warranty

Model	DC output	Current	Efficiency
MDR-100-12	12V	7.5A	83%
MDR-100-15	15V	6.6A	83%
MDR-100-24	24V	4.16A	86%

Model	DC output	Current	Efficiency
MDR-100-27	27V	3.7A	86%
MDR-100-36	36V	2.7A	86%
MDR-100-48	48V	2A	87%



Features:

- Input full range
- 85-264VAC/120~370VDC
- 47-63Hz
- Working temp:-10~+50°C
- Dimension:65.5*125.5*100MM
- Weight:0.8KGS
- 3 years warranty



Features:

- Input full range
- 85-264VAC/120~370VDC
- 47-63Hz
- Working temp:-10~+50°C
- Dimension:125.5*125.5*100MM
- Weight:1.2KGS
- 3 years warranty

Model	DC output	Current	Efficiency
DR-120-12	12V	10A	80%
DR-120-15	15V	8A	81%
DR-120-24	24V	5A	84%
DR-120-48	48V	2.5A	85%

Model	DC output	Current	Efficiency
DR-240-12	12V	20A	83%
DRP-240-24	24V	10A	84%
DRP-240-36	36V	6.66A	85%
DRP-240-48	48V	5A	85%

LRS series power supply



- Features:
- Input full range
 - 85-264VAC/120~370VDC
 - 47-63Hz
 - Working temp:-10~+50°C
 - Dimension:22.5*90*100MM
 - Weight:0.17KGS
 - 3 years warranty

Model	DC output	Current	Efficiency
LRS-35-12	12V	3A	84%
LRS-35-24	24V	1.5A	86%
LRS-35-36	36V	1A	87%
LRS-35-48	48V	0.8A	87%



- Features:
- Input full range
 - 85-264VAC/120~370VDC
 - 47-63Hz
 - Working temp:-20~+70°C
 - Dimension:99*82*30MM
 - Weight:0.23KGS
 - 3 years warranty

Model	DC output	Current	Efficiency
LRS-60-12	12V	5A	84%
LRS-60-15	15V	4A	84%
LRS-60-24	24V	2.5A	86%
LRS-60-48	48V	1.25A	87%



- Features:
- Input full range
 - 85-264VAC/120~370VDC
 - 47-63Hz
 - Working temp:-20~+70°C
 - Dimension:129*97*30MM
 - Weight:0.34KGS
 - 3 years warranty

Model	DC output	Current	Efficiency
LRS-100-12	12V	8.5A	86%
LRS-100-24	24V	4.5A	87%
LRS-100-36	36V	2.7A	88%
LRS-100-48	48V	2.3A	88%



- Features:
- Input full range
 - 85-264VAC/120~370VDC
 - 47-63Hz
 - Working temp:-20~+70°C
 - Dimension:99*82*30MM
 - Weight:0.23KGS
 - 3 years warranty

Model	DC output	Current	Efficiency
LRS-50-12	12V	4.2A	84%
LRS-50-24	24V	2.2A	86%
LRS-50-36	36V	1.3A	87%
LRS-50-48	48V	1.1A	87%



- Features:
- Input full range
 - 85-264VAC/120~370VDC
 - 47-63Hz
 - Working temp:-20~+70°C
 - Dimension:99*97*30MM
 - Weight:0.3KGS
 - 3 years warranty

Model	DC output	Current	Efficiency
LRS-75-12	12V	6A	86%
LRS-75-24	24V	3.2A	87%
LRS-75-36	36V	2A	88%
LRS-75-48	48V	1.6A	88%



- Features:
- Input full range
 - 85-264VAC/120~370VDC
 - 47-63Hz
 - Working temp:-20~+70°C
 - Dimension:129*97*30MM
 - Weight:0.34KGS
 - 3 years warranty

Model	DC output	Current	Efficiency
LRS-120-12	12V	10A	86%
LRS-120-15	15V	8A	86%
LRS-120-24	24V	5A	87%
LRS-120-48	48V	2.5A	87%

LRS series power supply



- Features:
- Input full range
 - 85-264VAC/120~370VDC
 - 47-63Hz
 - Working temp:-20~+70°C
 - Dimension:159*97*30MM
 - Weight:0.48KGS
 - 3 years warranty

Model	DC output	Current	Efficiency
LRS-150-12	12V	12.5A	84%
LRS-150-24	24V	6.5A	86%
LRS-150-36	36V	4.1A	87%
LRS-150-48	48V	3.3A	88%



- Features:
- Input full range
 - 85-264VAC/120~370VDC
 - 47-63Hz
 - Working temp:-20~+70°C
 - Dimension:215*115*30MM
 - Weight:0.66KGS
 - 3 years warranty

Model	DC output	Current	Efficiency
LRS-250-12	12V	20A	86%
LRS-250-15	15V	16A	86%
LRS-250-24	24V	10A	87%
LRS-250-48	48V	5A	88%



- Features:
- Input full range
 - 85-264VAC/120~370VDC
 - 47-63Hz
 - Working temp:-20~+70°C
 - Dimension:215*115*30MM
 - Weight:0.76KGS
 - 3 years warranty

Model	DC output	Current	Efficiency
LRS-350-36	36V	9.7A	86%
LRS-350-48	48V	7.3A	87%
LRS-350-60	60V	5.83A	88%
LRS-350-70	70V	5A	88%



- Features:
- Input full range
 - 85-264VAC/120~370VDC
 - 47-63Hz
 - Working temp:-20~+70°C
 - Dimension:129*97*30MM
 - Weight:0.34KGS
 - 3 years warranty

Model	DC output	Current	Efficiency
LRS-200-12	12V	17A	84%
LRS-200-24	24V	8.8A	86%
LRS-200-36	36V	5.5A	87%
LRS-200-48	48V	4.4A	88%



- Features:
- Input full range
 - 85-264VAC/120~370VDC
 - 47-63Hz
 - Working temp:-20~+70°C
 - Dimension:215*115*30MM
 - Weight:0.76KGS
 - 3 years warranty

Model	DC output	Current	Efficiency
LRS-350-12	12V	29A	83%
LRS-350-15	15V	23.2A	84%
LRS-350-24	24V	14.6A	86%
LRS-350-27	27V	12.9A	87%



- Features:
- Input full range
 - 85-264VAC/120~370VDC
 - 47-63Hz
 - Working temp:-20~+70°C
 - Dimension:215*115*30MM
 - Weight:0.76KGS
 - 3 years warranty

Model	DC output	Current	Efficiency
LRS-400-12	12V	33A	83%
LRS-400-15	15V	26.7A	84%
LRS-400-24	24V	16.5A	85%
LRS-400-48	48V	8.3A	86%

LRS series power supply



- Features:
- Input full range
 - 85-264VAC/120~370VDC
 - 47-63Hz
 - Working temp:-20~+70°C
 - Dimension:215*115*50MM
 - Weight:1KGS
 - 3 years warranty



- Features:
- Input full range
 - 85-264VAC/120~370VDC
 - 47-63Hz
 - Working temp:-20~+70°C
 - Dimension:215*115*50MM
 - Weight:1KGS
 - 3 years warranty

Model	DC output	Current	Efficiency
LRS-500-12	12V	40A	86%
LRS-500-24	24V	20A	87%
LRS-500-36	36V	14A	88%
LRS-500-48	48V	10A	88%
LRS-500-12	12V	40A	86%

Model	DC output	Current	Efficiency
LRS-600-12	12V	40A	83%
LRS-600-24	24V	25A	84%
LRS-600-36	36V	16.7A	85%
LRS-600-48	48V	12.5A	86%

D series dual output power supply



- Features:
- AC Input
 - 90-132VAC/180~264VDC
 - By switch/47-63Hz
 - Working temp:-10~+50°C
 - Dimension:129*98*38MM
 - Weight:0.4KGS
 - 3 years warranty



- Features:
- AC Input
 - 90-132VAC/180~264VDC
 - By switch/47-63Hz
 - Working temp:-10~+50°C
 - Dimension:159*98*38MM
 - Weight:0.55KGS
 - 3 years warranty

Model	DC output	Current	Efficiency
D-30A	5V/12V	4A/1A	72%
D-30B	5V/24V	2A/1A	74%
D-30C	12V/-12V	1.5A/1A	74%
D-30F	12V/24V	1A/1A	75%

Model	DC output	Current	Efficiency
D-50A	5V/12V	6A/2A	73%
D-50B	5V/24V	6A/1A	73%
D-50C	12V/-12V	2A/2A	75%
D-50F	12V/24V	2A/1A	76%

AD series power supply with battery charging function(UPS)



- Features:
- Input full range
 - 85-264VAC/120~370VDC
 - 47-63Hz
 - Working temp:-10~+60°C
 - Dimension:159*98*38MM
 - Weight:0.49KGS
 - 3 years warranty



- Features:
- Input full range
 - 85-264VAC/120~370VDC
 - 47-63Hz
 - Working temp:-10~+60°C
 - Dimension:199*110*50MM
 - Weight:0.76KGS
 - 3 years warranty

Model	DC output	Current	Efficiency
AD-55A	13.8V/13.4V	3.5A/0.23A	71%
AD-55B	27.6V/26.5V	1.8A/0.16A	74%

Model	DC output	Current	Efficiency
AD-155A	13.8V/13.3V	9.5A/0.5A	80%
AD-155B	27.6V/27.1V	4.5A/0.5A	84%
AD-155C	54V/53.5V	2.3A/0.2A	84%



- Features:
- Input full range
 - 85-264VAC/120~370VDC
 - 47-63Hz
 - Working temp:-10~+50°C
 - Dimension:159*98*38MM
 - Weight:0.55KGS
 - 3 years warranty



- Features:
- AC Input
 - 90-132VAC/180~264VDC
 - By switch/47-63Hz
 - Working temp:-10~+50°C
 - Dimension:199*110*50MM
 - Weight:0.9KGS
 - 3 years warranty

Model	DC output	Current	Efficiency
D-60A	5V/12V	4A/3A	73%
D-60B	5V/24V	3A/1.8A	76%
D-60C	12V/-12V	2.5A/2.5A	75%
D-60F	12V/24V	2A/1.5A	76%

Model	DC output	Current	Efficiency
D-120A	5V/12V	12A/5A	76%
D-120B	5V/24V	6A/4A	78%
D-120C	12V/-12V	5A/5A	80%
D-120F	12V/24V	5A/2.5A	80%

Q series qual series power supply



- Features:
- Input full range
 - 85-264VAC/120~370VDC
 - 47-63Hz
 - Working temp:-10~+50°C
 - Dimension:159*98*38MM
 - Weight:0.55KGS
 - 3 years warranty



- Features:
- Input full range
 - 85-264VAC/120~370VDC
 - 47-63Hz
 - Working temp:-10~+50°C
 - Dimension:199*110*50MM
 - Weight:0.9KGS
 - 3 years warranty

Model	DC output	Current	Efficiency
Q-60B	5V/12V/-5V/-12V	5.5A/2A 0.5A/0.5A	70%
Q-60C	5V/15V/-5V/-15V	5.5A/1.5A 0.5A/0.5A	72%
Q-60D	5V/12V/24V/-12V	4A/1A 1A/0.5A	75%

Model	DC output	Current	Efficiency
Q-120B	5V/12V/-5V/-12V	11A/4A 1A/1A	77%
Q-120C	5V/15V/-5V/-15V	10A/3.5A 1A/1A	76%
Q-120D	5V/12V/24V/-12V	8A/2A 2A/1A	80%

T series triple output power supply



- Features:
- AC Input
 - 90-132VAC/180~264VDC
 - By switch/47-63Hz
 - Working temp:-10~+50°C
 - Dimension:129*98*38MM
 - Weight:0.4KGS
 - 3 years warranty



- Features:
- AC Input
 - 90-132VAC/180~264VDC
 - By switch/47-63Hz
 - Working temp:-10~+50°C
 - Dimension:159*98*38MM
 - Weight:0.55KGS
 - 3 years warranty

Model	DC output	Current	Efficiency
T-30A	5V/12V/-5V	3A/1A/0.5A	70%
T-30B	5V/12V/-12V	3A/1A/0.5A	72%
T-30C	5V/15V/-15V	3A/0.5A/0.5A	72%
T-30D	5V/12V/24V	3A/0.5A/0.5A	72%

Model	DC output	Current	Efficiency
T-50A	5V/12V/-5V	7A/1A/1A	66%
T-50B	5V/12V/-12V	5A/1A/1A	69%
T-50C	5V/15V/-15V	4A/1A/1A	71%
T-50D	5V/12V/24V	3A/1A/1A	72%

T series triple output power supply



- Features:
- AC Input
 - 90-132VAC/180~264VDC
 - By switch/47-63Hz
 - Working temp:-10~+50°C
 - Dimension:159*98*38MM
 - Weight:0.55KGS
 - 3 years warranty



- Features:
- AC Input
 - 90-132VAC/180~264VDC
 - By switch/47-63Hz
 - Working temp:-10~+50°C
 - Dimension:199*110*50MM
 - Weight:0.9KGS
 - 3 years warranty

Model	DC output	Current	Efficiency
T-60A	5V/12V/-5V	5A/2.5A/0.5A	72%
T-60B	5V/12V/-12V	5A/2.5A/0.5A	72%
T-60C	5V/15V/-15V	5A/2A/0.5A	72%
T-60D	5V/12V/24V	5A/2.5A/0.5A	72%

Model	DC output	Current	Efficiency
T-120A	5V/12V/-5V	11A/5A/1A	77%
T-120B	5V/12V/-12V	11A/4.5A/1A	77%
T-120C	5V/15V/-15V	10A/3.5A/1A	76%
T-120D	5V/12V/24V	8A/2.5A/2A	80%

MS series mini type power supply



- Features:
- Input full range
 - 85-264VAC/120~370VDC
 - 47-63Hz
 - Working temp:-10~+50°C
 - Dimension:78*48*21MM
 - Weight:0.15KGS
 - 3 years warranty



- Features:
- Input full range
 - 85-264VAC/120~370VDC
 - 47-63Hz
 - Working temp:-10~+50°C
 - Dimension:97*58*25MM
 - Weight:0.19KGS
 - 3 years warranty

Model	DC output	Current	Efficiency
MSF-10-5	5V	2A	71%
MSF-10-12	12V	1A	73%
MSF-10-15	15V	0.8A	74%
MSF-10-24	24V	0.5A	75%

Model	DC output	Current	Efficiency
MSF-20-5	5V	4A	72%
MSF-20-12	12V	2A	74%
MSF-20-15	15V	1.6A	74%
MSF-20-24	24V	1A	76%

SCN series parallel power supply



- Features:
- AC Input
 - 90-132VAC/180~264VDC
 - By switch/47-63Hz
 - Working temp:-10~+50°C
 - Dimension:291*132*68MM
 - Weight:2.65KGS
 - 3 years warranty



- Features:
- AC Input
 - 90-132VAC/180~264VDC
 - By switch/47-63Hz
 - Working temp:-10~+50°C
 - Dimension:291*132*68MM
 - Weight:2.65KGS
 - 3 years warranty

Model	DC output	Current	Efficiency
SCN-800-12	12V	66A	80%
SCN-800-24	24V	33A	85%
SCN-800-36	36V	22A	85%
SCN-800-48	48V	17A	87%

Model	DC output	Current	Efficiency
SCN-1000-12	12V	80A	80%
SCN-1000-24	24V	42A	85%
SCN-1000-36	36V	28A	86%
SCN-1000-48	48V	21A	87%



- Features:
- Input full range
 - 85-264VAC/120~370VDC
 - 47-63Hz
 - Working temp:-10~+50°C
 - Dimension:84*58*38MM
 - Weight:0.21KGS
 - 3 years warranty



- Features:
- Input full range
 - 85-264VAC/120~370VDC
 - 47-63Hz
 - Working temp:-10~+50°C
 - Dimension:84*58*38MM
 - Weight:0.21KGS
 - 3 years warranty

Model	DC output	Current	Efficiency
MS-15-5	5V	3A	68%
MS-15-12	12V	1.3A	71%
MS-15-24	24V	0.7A	75%
MS-15-48	48V	0.3A	75%

Model	DC output	Current	Efficiency
MS-25-5	5V	5A	70%
MS-25-12	12V	2.1A	75%
MS-25-24	24V	1.1A	7%
MS-25-48	48V	0.52A	78%



- Features:
- AC Input
 - 90-132VAC/180~264VDC
 - By switch/47-63Hz
 - Working temp:-10~+50°C
 - Dimension:291*132*136MM
 - Weight:5.3KGS
 - 3 years warranty



- Features:
- AC Input
 - 90-132VAC/180~264VDC
 - By switch/47-63Hz
 - Working temp:-10~+50°C
 - Dimension:291*132*136MM
 - Weight:5.3KGS
 - 3 years warranty

Model	DC output	Current	Efficiency
SCN-1200-12	12V	100A	80%
SCN-1200-24	24V	50A	82%
SCN-1200-36	36V	33A	84%
SCN-1200-48	48V	25A	85%

Model	DC output	Current	Efficiency
SCN-1500-12	12V	125A	80%
SCN-1500-24	24V	62.5A	81%
SCN-1500-36	36V	41A	83%
SCN-1500-48	48V	32A	84%



- Features:
- Input full range
 - 85-264VAC/120~370VDC
 - 47-63Hz
 - Working temp:-10~+50°C
 - Dimension:84*58*38MM
 - Weight:0.22KGS
 - 3 years warranty



- Features:
- Input full range
 - 85-264VAC/120~370VDC
 - 47-63Hz
 - Working temp:-10~+50°C
 - Dimension:111*78*36MM
 - Weight:0.27KGS
 - 3 years warranty

Model	DC output	Current	Efficiency
MS-35-5	5V	6A	77%
MS-35-12	12V	3A	83%
MS-35-24	24V	1.5A	84%
MS-35-48	48V	0.73A	84%

Model	DC output	Current	Efficiency
MS-50-5	5V	10A	80%
MS-50-12	12V	4.2A	82%
MS-50-24	24V	2.1A	84%
MS-50-48	48V	1.04A	84%

MS series mini type power supply



- Features:
- Input full range
 - 85-264VAC/120~370VDC
 - 47-63Hz
 - Working temp:-10~+50°C
 - Dimension:111*78*36MM
 - Weight:0.27KGS
 - 3 years warranty



- Features:
- Input full range
 - 85-264VAC/120~370VDC
 - 47-63Hz
 - Working temp:-10~+50°C
 - Dimension:111*78*36MM
 - Weight:0.27KGS
 - 3 years warranty



- Features:
- AC Input
 - 90-132VAC/180~264VDC
 - By switch/47-63Hz
 - Working temp:-10~+50°C
 - Dimension:98*97*35MM
 - Weight:0.3KGS
 - 3 years warranty



- Features:
- AC Input
 - 90-132VAC/180~264VDC
 - By switch/47-63Hz
 - Working temp:-10~+50°C
 - Dimension:98*97*35MM
 - Weight:0.3KGS
 - 3 years warranty

Model	DC output	Current	Efficiency
MS-60-12	12V	5A	82%
MS-60-15	15V	4A	83%
MS-60-24	24V	2.5A	84%
MS-60-48	48V	1.25A	84%

Model	DC output	Current	Efficiency
MS-75-12	12V	6A	82%
MS-75-15	15V	5A	83%
MS-75-24	24V	3A	84%
MS-75-48	48V	1.56A	84%

Model	DC output	Current	Efficiency
S-15-5	5V	3A	65%
S-15-12	12V	1.3A	68%
S-15-24	24V	0.7A	72%
S-15-48	48V	0.3A	72%

Model	DC output	Current	Efficiency
S-25-5	5V	5A	65%
S-25-12	12V	2.1A	68%
S-25-24	24V	1.1A	72%
S-25-48	48V	0.52A	72%



- Features:
- AC Input
 - 90-132VAC/180~264VDC
 - By switch/47-63Hz
 - Working temp:-10~+50°C
 - Dimension:159*98*38MM
 - Weight:0.55KGS
 - 3 years warranty



- Features:
- AC Input
 - 90-132VAC/180~264VDC
 - By switch/47-63Hz
 - Working temp:-10~+50°C
 - Dimension:159*98*38MM
 - Weight:0.55KGS
 - 3 years warranty



- Features:
- AC Input
 - 90-132VAC/180~264VDC
 - By switch/47-63Hz
 - Working temp:-10~+50°C
 - Dimension:129*98*38MM
 - Weight:0.4KGS
 - 3 years warranty



- Features:
- AC Input
 - 90-132VAC/180~264VDC
 - By switch/47-63Hz
 - Working temp:-10~+50°C
 - Dimension:159*98*38MM
 - Weight:0.5KGS
 - 3 years warranty

Model	DC output	Current	Efficiency
MS-100-5	5V	20A	83%
MS-100-12	12V	8.5A	84%
MS-100-24	24V	4.5A	86%
MS-100-48	48V	2.08A	86%

Model	DC output	Current	Efficiency
MS-120-12	12V	10A	81%
MS-120-24	24V	5A	84%
MS-120-36	36V	3.3A	84%
MS-120-48	48V	2.5A	84%

Model	DC output	Current	Efficiency
S-35-5	5V	7A	70%
S-35-12	12V	3A	76%
S-35-24	24V	1.5A	78%
S-35-48	48V	0.72A	78%

Model	DC output	Current	Efficiency
S-50-5	5V	10A	71%
S-50-12	12V	4.2A	78%
S-50-24	24V	2.1A	82%
S-50-48	48V	1.04A	82%



- Features:
- AC Input
 - 90-132VAC/180~264VDC
 - By switch/47-63Hz
 - Working temp:-10~+50°C
 - Dimension:111*98*38MM
 - Weight:0.55KGS
 - 3 years warranty



- Features:
- AC Input
 - 90-132VAC/180~264VDC
 - By switch/47-63Hz
 - Working temp:-10~+50°C
 - Dimension:215*115*50MM
 - Weight:1KGS
 - 3 years warranty



- Features:
- AC Input
 - 90-132VAC/180~264VDC
 - By switch/47-63Hz
 - Working temp:-10~+50°C
 - Dimension:159*98*38MM
 - Weight:0.5KGS
 - 3 years warranty



- Features:
- AC Input
 - 90-132VAC/180~264VDC
 - By switch/47-63Hz
 - Working temp:-10~+50°C
 - Dimension:159*98*38MM
 - Weight:0.55KGS
 - 3 years warranty

Model	DC output	Current	Efficiency
MS-150-12	12V	12.5A	83%
MS-150-15	15V	10A	84%
MS-150-24	24V	6.5A	86%
MS-150-48	48V	3.13A	86%

Model	DC output	Current	Efficiency
MS-500-12	12V	40A	86%
MS-500-24	24V	20A	87%
MS-500-36	36V	14A	88%
MS-500-48	48V	10A	88%

Model	DC output	Current	Efficiency
S-60-5	5V	12A	72%
S-60-12	12V	5A	78%
S-60-24	24V	2.5A	82%
S-60-48	48V	1.25A	82%

Model	DC output	Current	Efficiency
S-75-12	12V	6A	78%
S-75-15	15V	5A	79%
S-75-24	24V	3.2A	82%
S-75-48	48V	1.5A	83%

S series single output power supply



- Features:
- AC Input
 - 90-132VAC/180~264VDC
 - By switch/47-63Hz
 - Working temp:-10~+50°C
 - Dimension:199*98*38MM
 - Weight:0.6KGS
 - 3 years warranty



- Features:
- AC Input
 - 90-132VAC/180~264VDC
 - By switch/47-63Hz
 - Working temp:-10~+50°C
 - Dimension:199*98*38MM
 - Weight:0.6KGS
 - 3 years warranty

S series single output power supply



- Features:
- AC Input
 - 90-132VAC/180~264VDC
 - By switch/47-63Hz
 - Working temp:-10~+50°C
 - Dimension:215*115*50MM
 - Weight:0.9KGS
 - 3 years warranty



- Features:
- AC Input
 - 90-132VAC/180~264VDC
 - By switch/47-63Hz
 - Working temp:-10~+50°C
 - Dimension:215*115*50MM
 - Weight:0.9KGS
 - 3 years warranty

Model	DC output	Current	Efficiency
S-100-5	5V	20A	78%
S-100-12	12V	8.5A	81%
S-100-24	24V	4.5A	84%
S-100-48	48V	2.1A	84%

Model	DC output	Current	Efficiency
S-120-12	12V	10A	81%
S-120-15	15V	8A	82%
S-120-24	24V	5A	84%
S-120-48	48V	2.5A	84%

Model	DC output	Current	Efficiency
S-250-12	12V	20A	79%
S-250-15	15V	16A	79%
S-250-24	24V	10A	81%
S-250-48	48V	5A	84%

Model	DC output	Current	Efficiency
S-320-12	12V	26.6A	83%
S-320-15	15V	13.3A	85%
S-320-24	24V	8.9A	85%
S-320-48	48V	6.6A	86%



- Features:
- AC Input
 - 90-132VAC/180~264VDC
 - By switch/47-63Hz
 - Working temp:-10~+50°C
 - Dimension:199*98*38MM
 - Weight:0.7KGS
 - 3 years warranty



- Features:
- AC Input
 - 90-132VAC/180~264VDC
 - By switch/47-63Hz
 - Working temp:-10~+50°C
 - Dimension:199*110*50MM
 - Weight:0.85KGS
 - 3 years warranty



- Features:
- AC Input
 - 90-132VAC/180~264VDC
 - By switch/47-63Hz
 - Working temp:-10~+50°C
 - Dimension:215*115*50MM
 - Weight:0.9KGS
 - 3 years warranty



- Features:
- AC Input
 - 90-132VAC/180~264VDC
 - By switch/47-63Hz
 - Working temp:-10~+50°C
 - Dimension:215*115*50MM
 - Weight:0.9KGS
 - 3 years warranty

Model	DC output	Current	Efficiency
S-145-5	5V	25A	75%
S-145-12	12V	12A	80%
S-145-24	24V	6A	83%
S-145-48	48V	3A	83%

Model	DC output	Current	Efficiency
S-150-5	5V	30A	78%
S-150-12	12V	12.5A	82%
S-150-24	24V	6.5A	85%
S-150-48	48V	3.13A	87%

Model	DC output	Current	Efficiency
S-350-5	5V	50A	73%
S-350-12	12V	29A	83%
S-350-24	24V	14.6A	85%
S-350-48	48V	7.3A	86%

Model	DC output	Current	Efficiency
S-400-5	5V	60A	73%
S-400-12	12V	33A	82%
S-400-24	24V	16.5A	83%
S-400-48	48V	8.3A	85%



- Features:
- AC Input
 - 90-132VAC/180~264VDC
 - By switch/47-63Hz
 - Working temp:-10~+50°C
 - Dimension:199*110*50MM
 - Weight:0.85KGS
 - 3 years warranty



- Features:
- AC Input
 - 90-132VAC/180~264VDC
 - By switch/47-63Hz
 - Working temp:-10~+50°C
 - Dimension:199*110*50MM
 - Weight:0.85KGS
 - 3 years warranty



- Features:
- AC Input
 - 90-132VAC/180~264VDC
 - By switch/47-63Hz
 - Working temp:-10~+50°C
 - Dimension:238*124*65MM
 - Weight:1.35KGS
 - 3 years warranty



- Features:
- AC Input
 - 90-132VAC/180~264VDC
 - By switch/47-63Hz
 - Working temp:-10~+50°C
 - Dimension:238*124*65MM
 - Weight:1.4KGS
 - 3 years warranty

Model	DC output	Current	Efficiency
S-200-5	5V	40A	79%
S-200-12	12V	16.5A	82%
S-200-24	24V	8.5A	83%
S-200-48	48V	4.2A	86%

Model	DC output	Current	Efficiency
S-201-5	5V	40A	74%
S-201-12	12V	16.5A	80%
S-201-24	24V	8.5A	83%
S-201-48	48V	4.2A	84%

Model	DC output	Current	Efficiency
S-500-12	12V	40A	83%
S-500-24	24V	20A	85%
S-500-36	36V	14A	86%
S-500-48	48V	10A	87%

Model	DC output	Current	Efficiency
S-600-12	12V	50A	83%
S-600-24	24V	25A	85%
S-600-36	36V	16.7A	86%
S-600-48	48V	12.5A	87%

S series single output power supply



- Features:
- AC Input
 - 90-132VAC/180~264VDC
 - By switch/47-63Hz
 - Working temp:-10~+50°C
 - Dimension:291*132*68MM
 - Weight:2.5KGS
 - 3 years warranty



- Features:
- AC Input
 - 90-132VAC/180~264VDC
 - By switch/47-63Hz
 - Working temp:-10~+50°C
 - Dimension:291*132*68MM
 - Weight:2.5KGS
 - 3 years warranty

S series single output power supply



- Features:
- AC Input
 - 90-132VAC/180~264VDC
 - By switch/47-63Hz
 - Working temp:-10~+50°C
 - Dimension:215*115*50MM
 - Weight:0.9KGS
 - 3 years warranty

Model	DC output	Current	Efficiency
S-800-12	12V	66A	80%
S-800-24	24V	33A	85%
S-800-36	36V	22A	85%
S-800-48	48V	17A	87%

Model	DC output	Current	Efficiency
S-1000-12	12V	80A	80%
S-1000-24	24V	42A	85%
S-1000-36	36V	28A	85%
S-1000-48	48V	21A	87%

Model	DC output	Current	Efficiency
S-3000-24	24V	125A	85%
S-3000-36	36V	83.3A	85%
S-3000-48	48V	62.5A	87%
S-3000-60	60V	50A	88%



- Features:
- AC Input
 - 90-132VAC/180~264VDC
 - By switch/47-63Hz
 - Working temp:-10~+50°C
 - Dimension:291*132*68MM
 - Weight:2.5KGS
 - 3 years warranty



- Features:
- AC Input
 - 90-132VAC/180~264VDC
 - By switch/47-63Hz
 - Working temp:-10~+50°C
 - Dimension:291*132*68MM
 - Weight:2.5KGS
 - 3 years warranty

Model	DC output	Current	Efficiency
S-1200-12	12V	100A	80%
S-1200-24	24V	50A	82%
S-1200-36	36V	33A	84%
S-1200-48	48V	25A	85%

Model	DC output	Current	Efficiency
S-1500-12	12V	125A	80%
S-1500-24	24V	62.5A	81%
S-1500-36	36V	41A	83%
S-1500-48	48V	32A	84%

SC series power supply with battery charging function(UPS)



- Features:
- AC Input Full Range
 - 85-264VAC/UPS
 - Battery protection in low voltage
 - Working temp:-10~+50°C
 - Dimension:111*78*36MM
 - Weight:0.3KGS
 - 3 years warranty



- Features:
- AC Input Full Range
 - 85-264VAC/UPS
 - Battery protection in low voltage
 - Working temp:-10~+60°C
 - Dimension:129*98*38MM
 - Weight:0.52KGS
 - 3 years warranty

Model	DC output	Current	Efficiency
SC-35-12	CH1:13.8V CH2:13.4V	2A 0.5A	81%
SC-35-24	CH1:27.6V CH2:26.5V	1A 0.3A	83%

Model	DC output	Current	Efficiency
SC-60-12	CH1:13.8V CH2:13.4V	4A 3.5A	81%
SC-60-24	CH1:27.6V CH2:26.5V	2A 0.25A	83%



- Features:
- AC Input
 - 90-132VAC/180~264VDC
 - By switch/47-63Hz
 - Working temp:-10~+50°C
 - Dimension:291*132*136MM
 - Weight:5.3KGS
 - 3 years warranty



- Features:
- AC Input
 - 90-132VAC/180~264VDC
 - By switch/47-63Hz
 - Working temp:-10~+50°C
 - Dimension:291*132*136MM
 - Weight:5.3KGS
 - 3 years warranty

Model	DC output	Current	Efficiency
S-2000-24	24V	83.3A	85%
S-2000-36	36V	55.5A	85%
S-2000-48	48V	41.6A	87%
S-2000-60	60V	33.4A	88%

Model	DC output	Current	Efficiency
S-2400-24	24V	100A	85%
S-2400-36	36V	66.6A	85%
S-2400-48	48V	50A	87%
S-2400-60	60V	40A	88%



- Features:
- AC Input 90-132V/180-264V
 - By switch/47-63Hz
 - Battery protection in low voltage
 - Working temp:-10~+60°C
 - Dimension:159*98*38MM
 - Weight:0.56KGS
 - 3 years warranty



- Features:
- AC Input 90-132V/180-264V
 - By switch/47-63Hz
 - Battery protection in low voltage
 - Working temp:-10~+50°C
 - Dimension:199*98*38MM
 - Weight:0.6KGS
 - 3 years warranty

Model	DC output	Current	Efficiency
SC-120-12	CH1:13.8V CH2:13.4V	8A 0.5A	84%
SC-120-24	CH1:27.6V CH2:26.5V	4A 0.3A	86%

Model	DC output	Current	Efficiency
SC-180-12	CH1:12V CH2:13.8V	13.5A 1.5A	85%
SC-180-24	CH1:24V CH2:27.6V	6.5A 1A	87%

SC series power supply with battery charging function(UPS)



Features:

- AC Input 90-132V/180-264V
- By switch/47-63Hz
- Battery protection in low voltage
- Working temp:-10~+50°C
- Dimension:215*115*50MM
- Weight:1KGS
- 3 years warranty

Model	DC output	Current	Efficiency
SC-350-12	CH1:13.8V CH2:13.8V	21A 5A	84%
SC-350-24	CH1:27.6V CH2:27.6V	9A 5A	86%

SD series DC power supply



Features:

- AC Input
- 90-132VAC/180~264VDC
- By switch/47-63Hz
- Working temp:-10~+50°C
- Dimension:291*132*68MM
- Weight:2.5KGS
- 3 years warranty

Model	DC output	Current	Efficiency
SD-15-5	5V	3A	76%
SD-15-12	12V	1.25A	76%
SD-15-24	24V	0.63A	77%



Features:

- AC Input
- 90-132VAC/180~264VDC
- By switch/47-63Hz
- Working temp:-10~+50°C
- Dimension:291*132*68MM
- Weight:2.5KGS
- 3 years warranty

Model	DC output	Current	Efficiency
SD-25-5	5V	5A	72%
SD-25-12	12V	2.1A	75%
SD-25-24	24V	1.1A	78%



Features:

- AC Input
- 90-132VAC/180~264VDC
- By switch/47-63Hz
- Working temp:-10~+50°C
- Dimension:291*132*68MM
- Weight:2.5KGS
- 3 years warranty

Model	DC output	Current	Efficiency
SD-50-5	5V	10A	73%
SD-50-12	12V	4.2A	75%
SD-50-24	24V	2.1A	80%



Features:

- AC Input
- 90-132VAC/180~264VDC
- By switch/47-63Hz
- Working temp:-10~+50°C
- Dimension:291*132*68MM
- Weight:2.5KGS
- 3 years warranty

Model	DC output	Current	Efficiency
SD-100-5	5V	20A	75%
SD-100-12	12V	8.5A	77%
SD-100-24	24V	4.2A	81%

Reliability in every watt

Innovation that powers progress

Partnership beyond the product